



SKIOLD DISC MILLS



CAPACITY TON/HOUR

Type	SK2500		SK5000			SK10T		SK780	
kW:	5,5	7,5	15	22	30	55	75	160	200
Barley:	0,7-1,4	1-1,9	1,7-3,2	2,4-4,7	3-6	5-10	6-13	9-19,5	12-26
Wheat:	0,75-1,5	1-2	1,8-3,5	2,5-5	3,2-6,5	5-12	6-15	9-22,5	12-30
Maize:	0,5-1,5	0,7-2	2-3,5	2,5-5	3-6,5	5-12	6-15	9-22,5	12-30
Oats:	0,6-1	0,8-1,3	1,4-2,3	2-3,2	2,4-4,5	4-9	5-12	9-18	12-24
Peas:	0,5-1,5	0,75-2	2-3,5	2,5-5	3-6,5	4-9	5-12	9-18	12-24

SPECIFICATIONS

Type	SK2500	SK5000	SK10T	SK780
Disc diameter (outer):	300 mm	450 mm	550 mm	780 mm
Disc distance regulation:	Manual or automatic	Manual or automatic	Automatic	Automatic
Disc distance min./max.:	0 – 10 mm	0 – 10 mm	0 – 8 mm	0 – 9 mm
Inlet, round/square:	Ø100 / Ø150 mm	Ø150 mm	200 x 200 mm	Ø200 mm
Outlet, rectangular:	300 x 87 mm	482 x 101 mm	710 x 198 mm	945 x 295 mm
Feeding auger:	Optional (0,37 kW)	Optional (0,75 kW)	Yes (0,75 kW)	Yes (1,5 kW)
Main bearing greasing:	Manually	Manually	Automatic device	Automatic device
Temperature switch:	No	No	Yes	Yes
Noise level, approx.:	80 dB	80 dB	80 dB	80 dB
RPM:	3000	3000	3000	3000
Approx. weight:	120 kg	335 kg	1210 kg	4600 kg

In storage dry and well cleaned crops.
The capacity depends on the grinding fineness

